




Product Grade	Description
 <p>HT LR GREASE, NLGI 2 GRADE: 1930</p>	<ul style="list-style-type: none"> • Excellent EP, AW, Anti-rust property with ability to handle very high loads and shock loads. • Forms a film of solid lubricant that provides additional lubricity for all types of bearings, machine elements and industrial applications. • Serviceable Temperature: -30°C to 150°C • Pack Size: 1 & 21 Kg
 <p>X HT LR GREASE, NLGI 2 GRADE: 1931</p>	<ul style="list-style-type: none"> • Excellent EP, AW, Anti-rust properties with ability to handle very high temperature, loads and shock-loads. • Forms a film of solid lubricant that provides emergency lubrication for all types of bearings, machine elements and industrial applications. • Serviceable Temperature: -30°C to 200°C • Pack Size: 1& 21 Kg
 <p>HT MP GREASE, NLGI 2 GRADE: 1999</p>	<ul style="list-style-type: none"> • Excellent EP, AW Anti-rust & high temperature and water wash off resistance. • Excellent Release agent, thread compound, conductive paste and assembly paste all rolled in one. • Useful as a plunger lubricant in die casting application and lubrication of hinges , slideways, etc. • Serviceable Temperature: -30°C to 130/480°C • Pack Size: 1& 21 Kg

Product Grade	Description
 <p>WHITE PTFE GREASE, NLGI 2 GRADE: 1950</p>	<ul style="list-style-type: none"> • Excellent EP, AW, anti-rust properties. • Suitable for all types of bearings, machine elements and industrial applications. • Excellent coefficient of friction due to presence of PTFE. • Provides long life lubrication in many applications. • Serviceable Temperature: -30°C to 150°C • Pack Size: 1 & 21 Kg
 <p>RED PTFE GREASE, NLGI 2 GRADE: 1951</p>	<ul style="list-style-type: none"> • Excellent EP, AW, Anti-rust properties for all types of bearings, machine elements and industrial applications. • Excellent coefficient of friction due to presence of PTFE in lithium soap complex. • Provides long life lubrication in many applications. • Serviceable Temperature: -30°C to 200°C • Pack Size: 1& 21 Kg